LOG SPECIFICATIONS

SCALING: ALL SAWLOGS SCALED SCRIBNER RULE: Average diameter of the small end of the log.
- Metal logs or logs with evidence of metal will not be scaled and/or valued.
- Visible defects will be deducted accordingly.
- Logs are graded and scaled **as presented.**
- **CUT LOGS AS STRAIGHT AS POSSIBLE.**
- **Scaler's discretion on log grade and scale is final!!**

SIZE: Diameter
- Logs less than 10" on small end graded #3
- Any log that **cannot** be trimmed to 34" or less in diameter anywhere along its length will have a Maximum grade of #2.
- Logs over 34" not scaled.

Lengths
- Even lengths from 8' through 12' with 8" of trim – the exception 9'6" length logs are acceptable.
- 8 foot logs need 8" of trim; minimum length log is 7'6", maximum grade #2.

LOG PREPARATION: Logs must be fresh cut from live timber!!
- Please trim butt flairs and side knots flush to log. Trim stump pulls.
- **Sweepy, crooked, split or poorly prepared logs deducted at scaler's discretion and may not be scaled and/or valued. Deduction will be made for split logs and for excessive rot.**

* Excessive mineral a grade defect in Oak.
*Ash PX and Prime (50% or less heart). *Heavy ring gum is a defect in Cherry.
* **Maple with large brown hearts a grade defect. (50% or less heart)**
* No tapped Hard Maple accepted and/or valued. Silver or River maple logs will grade #3.

LOG GRADE DESCRIPTION

Veneer: Veneer Logs are scaled DOYLE RULE.
Lengths - 8', 9', 10', 12' with 6" trim; longer lengths are accepted as veneer providing whole log is veneer quality, avoid 16' lengths, 9'6", 10'6" and 12'6" are preferred lengths
- Gum, birdpeck and excessive sapwood a defect in Cherry veneer.
- Hard Maple Veneer must have brown heartwood ¼ or less. No 8 foot lengths.
- Ash Veneer must have brown heartwood 1/3 or less. - Mineral is a defect in Red Oak.

****VENEER LOGS ARE SUBJECT TO INSPECTION BY VENEER BUYER PRIOR TO PURCHASE****

SAWLOGS: LARGER AND LONGER LOGS – THE MORE DEFECT ALLOWED.

PRIME X: 15" and larger, clear, straight butt logs. **9'6" and longer**. Longer and larger logs may have a knot within 1 foot of end of log. 8'8" butt logs with zero defect can grade PX.

PRIME: 14" and larger on small end, 8'8" and longer, straight, and free of defect.
13" and larger on 10'6" and longer butt logs.
Second cut Prime's **must** be 14" and larger, with minimal defect.
LONGER AND LARGER logs may have one or two knots on same face within 1 foot of end of log.

#1 12" and larger on small end 8'8" and longer, straight, clear 3 faces. 11" butt logs clear 4 faces, 10' and longer make #1.

#2A 10"-11" butt logs 4 faces
8'6" and greater

#2B **10" + clear 2 faces**
11" + clear 3 faces
8'6" and greater

#3 Any log less than 10" on small end, excessively crooked and/or less than 2 clear faces.

ALL SPECIALTY LOGS ARE SCALED DOYLE RULE. PRICES SUBJECT TO CHANGE WITHOUT NOTICE

ASH SPECIALTY LOGS -
- Lengths: 9'6" and longer.
- 14" + small end diameter. Butt logs only
- **No defects**. 25% brown heartwood or less.

WHITE OAK SPECIALTY LOGS
- Lengths 9'6" and longer
- 16"+ small end diameter
- Clear, minimal defect.

HARD MAPLE SPECIALTY LOGS
- Lengths: 9'6" and longer, butt logs **ONLY**
- Diameter: 13" + small end diameter.
- 25% brown heartwood or less.
- Even growth, no ingrown bark.

CHERRY SPECIALTY LOGS
- Lengths 9'6" and longer, butt log only
- Diameter 13"+ small end diameter
- Minimal gum, 4 face clear

***** 9'6" LOGS ARE PREFERRED TO 8'6" LOGS*****

9/2018